

CPU-S OPEN



This **CPU-S OPEN** is the small stationary brother of the ECN-S. Exceptionally handy and advantageous high-pressure cleaner to be used as a fixed unit in workplaces, garages, at agricultural companies and in other sectors.

Compact construction and suitable for wall and floor assembly. On request optionally available as a version with float chamber.

EXCLUSIVE TECHNOLOGIES



Radial high-pressure pump



Motor with low speed



5 Year warranty

PRODUCT SPECIFICATIONS

- A powder-lacquered steel frame → prevention from corrosion and robust

TECHNICAL SPECIFICATIONS

- Radial high pressure pump with 3 ceramic plungers and stainless steel valves → fewer vibrations and less noise
- Electric engine at low speed
- Automatic start/stop system with shut-down-delay
- Pressure gauge
- Coarse particle filter
- On/Off switch
- Pressure control valve to adjust the operating pressure
- Detergent injector (not on models with (!))














Note:

Monophase machines work as standard at 1 x 230 V - 50 Hz.

3-phase machines work standard at 3 x 400 V - 50 Hz.

Other versions on request.

MODELS

												
Code	Description	bar	l/h	°C	V	A	kW	rpm	m	mm	kg	
1.192.068	CPU-S OPEN 130/10	30 - 130	600	40	3	1x230 V 50 Hz	13	1450	5	780 x 450 x 490	65	040
1.192.193	CPU-S OPEN 160/20	30 - 160	1200	40	7	3x400 - 50 Hz	11	1450	5	780 x 450 x 490	80	075
1.192.293	CPU-S OPEN 210/15	30 - 210	900	40	7	3x400 - 50 Hz	11	1450	5	780 x 450 x 490	80	045

OPTIONAL ACCESSORIES

Code	Item description
1.208.630.xxxxx	Double stainless steel spray lance with low and high pressure nozzle and rotating quick coupling (only on < 320 bar and < 41 l/min) → chemicals and stepless pressure regulation
1.211.5xx	High pressure gun with swivel → large manoeuvrability of the wash gun
1.205.520.020	High pressure hose (5/16", 10 m) → extended reach
1.205.520.xxx	High pressure extension hoses with quick release (10-25 m, ≤ 250 bar)
1.208.828.xxxxx	Flexible spray lance with high pressure nozzle (850 mm, ≤ 200 bar)
1.258.220.xxxxx	High pressure grit blasting lance with flat jet nozzle and suction hose (900 mm, ≤ 250 bar)
1.244.251	Foam lance with 1 l tank and quick release (200 mm, ≤ 250 bar)