

# HOTBOX-GK



The standard steam function with anti-scale system makes the **DiBO HOTBOX -GK 50/10 (30/5)** the ultimate multifunctional high-pressure cleaner. It is the smallest mobile hot water high-pressure cleaner in the DiBO range.

But do not be misled by the word 'smallest', as the cleaning options are practically unlimited. The machine works on 220/230V, and in high-pressure mode you can work with an operating pressure of 50 bar and temperatures ranging from 110 °C. With the **steam function 140 °C and 30 bar** the machine can be used for:

- specially for roof and façade cleaning
- the removal of graffiti, chewing gum and lichen
- delicate cleaning of gravestones and monuments
- alternative form of weed control\* cleaning vehicles and degreasing (engine) parts during maintenance work in the garage

## EXCLUSIVE TECHNOLOGIES



Modern design



High quality materials



Robust frame



GreenBoiler



Radial high-pressure pump



Motor with low speed



Steam function



10h use



5 Year warranty

## PRODUCT SPECIFICATIONS

- A powder-lacquered steel frame → prevention from corrosion and robust
- High quality materials: UV-resistant and thick walled rotation casted polyethylene in combination with stainless steel → very solid, colourfast and scratch protection and no corrosion
- 2 integrated lance holders → ergonomic
- Easy to use control panel
- Simple control panel → easy to use
- 2 industrial casters with wheel brake system → stability and manoeuvrability
- Large and sturdy wheels → mobile













## STANDARD EQUIPMENT

Code	Item description
1.228.183	Steam lance
1.216.729.xxxxx	Single stainless steel lance with high pressure nozzle and rotating quick coupling (≤ 250 bar)
1.211.518	High-pressure gun (310 bar - 40 l - complete)
1.274.560.023	Extension hose 25 metres max. 600 bar

## TECHNICAL SPECIFICATIONS

- High-tech heating system\* 70 kW GreenBoiler for a greater efficiency > 92%\* 18% fuel saving\* Low CO2 emission\* Low maintenance cost
- Radial high pressure pump with 3 ceramic plungers and stainless steel valves → fewer vibrations and less noise
- Low-speed electric motor (1450 rpm) → less wear
- Automatic start/stop system with shut-down-delay
- Anti-limescale system with 2 l tank
- Temperature adjustment
- Pressure gauge
- Direct-in
- Thermal engine protection
- Dry-run protection
- Flame protection
- Automatic water softening system
- Main switch ON/OFF
- Note: Monophase machines work as standard at 1 x 230 V - 50 Hz. 3-phase machines work standard at 3 x 400 V - 50 Hz.\*Other versions on request.\*

## MODELS

											
Code	Description	bar	l/h	°C	kW	kW	rpm	l	m	mm	kg
1.174.975	HOTBOX-GK 50/10 (30/5)	50-30	600-420	max. 110° (HD) / 140° at 30 bar (SF)	1,5	70	1450	2	25	900 x 700 x 1150	210