

HOTBOX



The **DiBO HOTBOX** allows you to make a professional hot water equipment from your cold water high- pressure cleaner.

This mobile burner module can be connected easily between the cold water high- pressure cleaner and the high-pressure hose. It works completely independent and heats the water to a maximum level of 150° C.

This makes it extremely useful to a whole range of cleaning jobs, for which the use of hot water is to be necessary for an effective and thorough cleaning, a.o. in the field of agriculture for stable and shed cleaning, for industrial use and in private accommodations for swimming pool cleaning, etc. The HOTBOX is being fed by a high-pressure cleaner of by another water pump with a minimum working pressure of 40 bar.

EXCLUSIVE TECHNOLOGIES



Modern design



High quality materials



Robust frame



GreenBoiler



5 Year warranty

PRODUCT SPECIFICATIONS

- Modern ergonomic design
- A powder-lacquered steel frame → prevention from corrosion and robust
- High quality materials: UV-resistant and thick walled rotation casted polyethylene in combination with stainless steel → very solid, colourfast and scratch protection and no corrosion
- 2 industrial casters with wheel brake system → stability and manoeuvrability
- Large and sturdy wheels → mobile
- Easy to use operation panel with ON/OFF switch and thermostat

STANDARD EQUIPMENT

Code	Item description
1.821.119	High pressure hose with quick coupling (3/8", 2 m, 220 bar)
1.821.148	High pressure hose with quick coupling (3/8", 2 m, 500 bar)

TECHNICAL SPECIFICATIONS

- 70 kW GreenBoiler
 - for a greater efficiency > 92%
 - 18% fuel saving
 - Low CO2 emission
 - Low maintenance cost
- Single phase engine, directly connected to the fan and to the fuel engine
- Safety precautions: equipped with a pressure switch, a safety valve and a flow meter in order to check if the machine does not run dry

- Inlet: 3/8" outer screw thread and outlet: connecting piece: V-part














Note:

Monophase machines work as standard at 1 x 230 V-50 Hz.

3-phase machines work standard at 3 x 400 V - 50 Hz.

Other versions on request.

MODELS

												
Code	Description	bar	l/h	°C	kW	V	A	kW	l	m	mm	kg
1.173.205	HOTBOX 220	220	360 - 1320	30 - 150	0,3	1 x 230 - 50 Hz	2	70	27	2	900 x 700 x 1150	155
1.173.207	HOTBOX 500	500	360 - 1080	30 - 150	0,3	1 x 230 - 50 Hz	2	70	27	2	900 x 700 x 1150	160

