

# PTL-L



Due to its on-board power source and self-contained operation, the **PTL-L** cold water high-pressure cleaner is easy to use even in places where there is no electricity.

Suitable for intensive daily use.

## EXCLUSIVE TECHNOLOGIES



Modern design



High quality materials



Robust frame



Radial high-pressure pump



Automatic idling speed



Motor pump coupling using reduction gearbox



5 Year warranty



12h use

## PRODUCT SPECIFICATIONS

- Modern ergonomic design
- A powder-lacquered steel frame → prevention from corrosion and robust
- High quality materials: UV-resistant and thick walled rotation casted polyethylene in combination with stainless steel → very solid, colourfast and scratch protection and no corrosion
- 2 integrated lance holders → ergonomic
- 2 integrated brackets
- 4 sturdy wheels with brake
- Quick-connect couplings for replacing accessories
- Integrated lifting eye, so the machines can also easily be lifted by a crane

## STANDARD EQUIPMENT

Code	Item description
1.216.749.5035	Single stainless steel lance with high pressure nozzle and rotating quick coupling (350 bar)
1.216.769.15030	Single stainless steel lance with high pressure nozzle and rotating quick coupling (500 bar)
1.208.749.xxxxx	Single lance with rotating high pressure nozzle → powerful water jet (only on 350 bar)
1.211.5xx	High pressure gun with swivel* → large manoeuvrability of the wash gun (*) depending on pressure and flow rate with or without swivel
1.208.xxx.020	High pressure hose (3/8", 10 m) → extended reach



1.211.5xx



1.208.xxx.020



1.216.749.5035 (350 bar)  
1.216.749.15030 (500 bar)



1.208.749.xxxxx

Subject to change

## TECHNICAL SPECIFICATIONS

- Petrol engine with electric starting with integrated fuel tank (EB)
- Radial high pressure pump with 3 ceramic plungers and stainless steel valves → fewer vibrations and less noise
- Engine/pump coupling via reduction gearbox
- Temperature protected by thermo valve
- Vibration dampers
- Pressure gauge
- Coarse particle filter
- Automatic idling → less consumption (\*)
- Low pressure entrance: GEKA-coupling



## MODELS

Code	Description	bar	l/h	°C	kW	l	m	mm	kg	
1.112.625	PTL-L 350/16 BE	350	960	40	17,2	6,5	10	1193x773x1054	137	035
1.112.825	PTL-L 500/14 BE	500	840	40	17,2	6,5	10	1193x773x1054	137	025

## OPTIONAL EQUIPMENT

Code	Item description
1.212.091	Supplement for hour counter

## OPTIONAL ACCESSORIES

Code	Item description
1.212.028	Hose reel set with 20 m hose, for PTL-L ≤ 350 bar
1.212.048	Hose reel set with 40 m hose, for PTL-L ≤ 350 bar
1.208.560.xxx	High pressure extension hoses with quick release (10-25 m, ≤ 500 bar)
1.208.540.xxx	High pressure extension hoses with quick release (10-25 m, > 250 bar & ≤ 350 bar)
1.258.225.xxxxx	High pressure grit blasting lance with power jet hp nozzle and suction hose (900 mm, ≤ 350 bar & ≤ 500 bar)
1.258.229.xxxxx	High pressure grit blasting lance with flat jet nozzle and suction hose (900 mm, ≤ 350 bar & ≤ 500 bar)