

SG-55



Maximum hygiene, minimum effort: Meet the DiBO SG-55.

Are you looking for an effective solution for tough cleaning jobs in industry, hospitality or transport? The DiBO SG-55 is the ultimate powerhouse that makes no compromises. With an **steam pressure of 8 bar** and a **temperature of 180 °C**, it effortlessly removes even the most stubborn dirt while instantly eliminating bacteria and germs.

It thoroughly cleans and dries instantly, saving you valuable time without compromising on quality. Thanks to its powerful suction function, the SG-55 immediately extracts dissolved dirt and water residue. The result? A clinically clean surface that is immediately ready for use again.

It is powerful, reliable and designed for daily intensive use.

PRODUCT SPECIFICATIONS

Control panel with:

- digital indicator for boiler temperature
- Indicator light for:
 - Steam ready
 - Detergent lack
 - Power supply
- Steam output regulator
- Boiler switch
- Detergent switch
- Main switch

Standard vacuum cleaner in stainless steel structure
Automatic shutdown

STANDARD EQUIPMENT

Code	Item description
3.8007.IPIP40021	Steam hose with handgrip - 4 m
3.8007.MPVR40958	Hose extension length = 500 mm (2 pcs.)
3.8007.SPPV40060	Multipurpose floor brush
3.8007.SPPV40061	Carpet protection for multipurpose brush
3.8007.SPPV40062	Frame with bristles and rubber scrapers for multipurpose brush
3.8007.SPPV40063	Brush for window cleaning
3.8007.SPPV40064	Transparent Upholstery nozzle
3.8007.SPPV40065	Large suction nozzle and squeegee
3.8007.SPPV40066	Small suction nozzle
3.8007.SPPV40067	Steam lance
3.8007.SPPV40056	Small round brush with polyester bristles - Ø 28 mm
3.8007.SPPV40068	Round brush with polyester bristles, Ø 65 mm
3.8007.SPPV40069	Round brush with polyester bristles, Ø 40 mm
3.8007.SPPV40070	Round brush with stainless steel bristles, Ø 40 mm
3.8007.AZMC40024	Wrench for maintenance
3.8007.SPPV40058	Rectangular microfiber cloth




3.8007.IPIP40021



3.8007.MPVR40958



3.8007.SPPV40060



3.8007.SPPV40061



3.8007.SPPV40062

TECHNICAL SPECIFICATIONS

- Steam mass flow: 250 g/min
- Heat up time: < 5 min
- Heating capacity: 10,4 kW
- Boiler volume: 4,2 l
- Vacuum power: 1,4 kW
- Water tank: 15 l
- Detergent tank: 5 l

MODELS


									
Code	Description	bar	kW	°C	Ph	V	Hz	mm	kg
3.106.009	SG-55 S 8025 T	8	10,4	max. 180	3	400	50	800 x 550 x 1020	59,5



3.8007.SPPV40063



3.8007.SPPV40064



3.8007.SPPV40065



3.8007.SPPV40066



3.8007.SPPV40067